


# BLECP 2000 >80

BLECP2000024DC18120840000W05

Article no.: 171218

**BILTON**

FOCUSED  
ON  
LINEAR  
LIGHT



24  
V

Lamp voltage

50.0  
mm

Length of particular  
segments

120

Number of lamps per  
meter

2000  
lm

Luminous flux per meter

## TENDER TEXT

BL ECO+ 2000 LED strip 24VDC 18,1W/m IP20 CRI>80 4000K WHITE 5m LED module BLECP 2000 >80 Article 171218 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLECP 2000 >80 LED-strip has a luminous flux of 2000 lm at 18.1 W, resulting in an efficiency of 110 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 8000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 8.30 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.2 mm

## TOP-FEATURES

- //\_\_ Long line lengths and better stability due to double layer
- //\_\_ Guaranteed LED properties with guaranteed patent protection
- //\_\_ Current regulation via transistors
- //\_\_ To create a homogeneous light image, the band is populated with ###attribute.6040### LEDs per meter

24 V

>80

IP20

4000 K



# BLECP 2000 >80

**BLECP2000024DC18120840000W05**

Article no.: 171218

## MECHANICAL DATA

Net width [mm]	8.0
Net height [mm]	1.6
Net length [mm]	1000.0
Degree of protection (IP)	IP20
Colour	White
Net weight [g]	9.8
Distance [mm]	8.30
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

## ELECTRICAL DATA

Overall efficiency [lm/W]	110
Lamp power per meter [W]	18.1
Lamp voltage [V]	24
Voltage type	DC
Protection class	None

## LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	2000
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>80
Colour temperature [K]	4000
Energy efficiency class provided exchangeable built-in lamp	F

## CONNECTION

Number of poles	2
Conductor cross section [mm²]	0.50
Max. length [mm]	8000.0

## TEMPERATURE TECHNICAL DATA

Rated life time L80/B50 at 25 °C [h]	60000
Ambient temperature during operating [°C]	- 20 ... + 45
Ambient/storage temperature [°C]	- 5 ... + 55
Operation temperature at Tc [°C]	- 5 ... + 60

## PACKAGING INFORMATION

EAN	4250716942101
Article no.	171218

# BLECP 2000 >80

BLECP2000024DC18120840000W05

Article no.: 171218

Customs tariff number	94054239
Length [mm]	5000.0
Gross weight [g]	35.0
Gross height [mm]	18.0
Gross width [mm]	200.0
Gross length [mm]	200.0
State of origin	CN

\* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.biltongroup.com](http://www.biltongroup.com)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.biltongroup.com](http://www.biltongroup.com)