


# BLOPL 3000 >90

BLOPL3000024DC20520940000W05

Article no.: 102068

**BILTON**

FOCUSED  
ON  
LINEAR  
LIGHT



24  
V

Lamp voltage

3000  
lm

Luminous flux per meter

2000.0  
mm

Max. length

>90

Colour rendering index CRI

## TENDER TEXT

BL ONE+ 3000 LED strip 24VDC 20,5W/m IP20 CRI>90 4000K WHITE 5m LED module BLOPL 3000 >90 Article 102068 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLOPL 3000 >90 LED-strip has a luminous flux of 3000 lm at 20.5 W, resulting in an efficiency of 146 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 2000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 120°. All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 6.25 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

## TOP-FEATURES

//\_\_ Improvement of homogeneity by 20 additional LEDs per meter

//\_\_ Wide choice of light colors and lumen packages

//\_\_ Wide range of applications for linear lighting in white

//\_\_ With a maximum module length of up to 2000.0 mm long, linear lighting lines can be implemented

24 V

>90

IP20

4000 K



RoHS  
COMPLIANT  
2002/95/EC



# BLOPL 3000 >90

**BLOPL3000024DC20520940000W05**

Article no.: 102068

## MECHANICAL DATA

|                                    |            |
|------------------------------------|------------|
| Net width [mm]                     | 8.0        |
| Net height [mm]                    | 1.5        |
| Net length [mm]                    | 5000.0     |
| Degree of protection (IP)          | IP20       |
| Colour                             | White      |
| Net weight [g]                     | 49         |
| Distance [mm]                      | 6.25       |
| Distance relating to               | LED to LED |
| Length of particular segments [mm] | 50.0       |

## ELECTRICAL DATA

|                           |         |
|---------------------------|---------|
| Overall efficiency [lm/W] | 146     |
| Lamp power per meter [W]  | 20.5    |
| Lamp voltage [V]          | 24      |
| Input voltage range [V]   | 23 - 25 |
| Voltage type              | DC      |
| Protection class          | III     |

## LIGHT TECHNICAL DATA

|   |       |
|---|-------|
| Luminous flux per meter [lm]                                | 3000  |
| Beam angle [°]  | 120   |
| Colour consistency (McAdam ellipse)                         | SDCM3 |
| Colour rendering index CRI                                  | >90   |
| Colour temperature [K]                                      | 4000  |
| Energy efficiency class provided exchangeable built-in lamp | D     |

## CONNECTION

|                               |        |
|-------------------------------|--------|
| Number of poles               | 2      |
| Conductor cross section [mm²] | 0.50   |
| Max. length [mm]              | 2000.0 |

## TEMPERATURE TECHNICAL DATA

|   |               |
|---|---------------|
| Rated life time L80/B10 at 25 °C [h]      | 60000         |
| Ambient temperature during operating [°C] | - 20 ... + 45 |
| Ambient/storage temperature [°C]          | 0 ... + 60    |
| Operation temperature at Tc [°C]          | - 5 ... + 60  |

## PACKAGING INFORMATION

|     |               |
|-----|---------------|
| EAN | 4250716939675 |
|-----|---------------|

# BLOPL 3000 >90

**BLOPL3000024DC20520940000W05**

Article no.: 102068

|                       |          |
|-----------------------|----------|
| Article no.           | 102068   |
| Customs tariff number | 94054099 |
| Length [mm]           | 5000.0   |
| Gross weight [g]      | 175.0    |
| Gross height [mm]     | 18.0     |
| Gross width [mm]      | 200.0    |
| Gross length [mm]     | 200.0    |
| State of origin       | AT       |

\* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.biltongroup.com](http://www.biltongroup.com)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.biltongroup.com](http://www.biltongroup.com)