


Corner connector CRI>90

BLSMCCRNO19940NS

Article no.: 171130

BILTON
FOCUSED
ON
LINEAR
LIGHT



TENDER TEXT

BL SmartCore Corner connector compatible with BLONE 2019 (900/1300/2000/3000lm/m), CRI90 4000K, without sensors 12mm width

TOP-FEATURES

//__ Thanks to the corner feed, the light is not even interrupted at a 90 ° corner

//__ Compatible with BLO19 (BL ONE series - (900 / 1,300 / 2,000 / 3,000 lm/m)

24 V

>90

IP20

4000 K

Corner connector CRI>90

BLSMCCRNO19940NS

Article no.: 171130

MECHANICAL DATA

Net width [mm]	57.4
Net height [mm]	1.5
Net length [mm]	57.4
Degree of protection (IP)	IP20
Colour	White
Net weight [g]	1.8
Distance [mm]	7.14
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

ELECTRICAL DATA

Lamp voltage [V]	24
Voltage type	DC
Protection class	III

LIGHT TECHNICAL DATA

Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>90
Colour temperature [K]	4000

CONNECTION

Number of poles	2
Conductor cross section [mm²]	0.50

PACKAGING INFORMATION

EAN	4250716940626
Article no.	171130
Customs tariff number	94054099
Length [mm]	57.0
Gross weight [g]	1.8
State of origin	IT

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com