
BILTON AIR SIDE 450 2019

BLAIRS0450024DC14667827000W03

Article no.: 101351





24 V	450 lm	3000.0 mm	>80
Lamp voltage	Luminous flux per meter	Max. length	Colour rendering index CRI

TENDER TEXT

BILTONAIR SIDE 450 LED strip 24VDC 14,6W/m IP67 CRI>80 2700K WHITE 3m LED module BILTON AIR SIDE 450 2019 Article 101351 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 50000 h . The BILTON AIR SIDE 450 2019 LED-strip has a luminous flux of 450 lm at 14.6 W, resulting in an efficiency of 31 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 3000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP67 Smallest possible bending radius 200 mm Dimension (L x W x H): 3010.0 mm x 13.2 mm x 16.0 mm

TOP-FEATURES

//__ Homogeneously illuminated light line with no visible light points

//__ IP67 protection in highly flexible silicone jacket

//__ Unlimited freedom of design (flexibly deformable and separable)

24 V | >80 | IP67 | 2700 K | RoHS COMPLIANT 2002/95/EC | CE

Version: 20240329 // Errors and printing errors are reserved.
© BILTON International GmbH, Gewerbepark Harham 2, 5760 Saalfelden, Austria // Phone: +43 6582 71164 // Mail: office@biltongroup.com // www.biltongroup.com

BILTON AIR SIDE 450 2019

BLAIRS0450024DC14667827000W03
Article no.: 101351

MECHANICAL DATA

Net width [mm]	13.2
Net height [mm]	16.0
Net length [mm]	3010.0
Degree of protection (IP)	IP67
Colour	White
Distance [mm]	7.14
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

ELECTRICAL DATA

Overall efficiency [lm/W]	31
Lamp power per meter [W]	14.6
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Voltage type	DC
Protection class	None

LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	450
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>80
Colour temperature [K]	2700

CONNECTION

Number of poles	2
Conductor cross section [mm²]	0.50
Max. length [mm]	3000.0

TEMPERATURE TECHNICAL DATA

Rated life time L80/B10 at 25 °C [h]	50000
Ambient temperature during operating [°C]	- 20 ... + 45
Ambient/storage temperature [°C]	- 20 ... + 50

PACKAGING INFORMATION

EAN	4250716933284
Article no.	101351
Customs tariff number	94054039
Length [mm]	3010.0

© BILTON International GmbH, Gewerbepark Harham 2, 5760 Saalfelden, Austria // Phone: +43 6582 71164 // Mail: office@biltongroup.com // www.biltongroup.com

BILTON AIR SIDE 450 2019

BLAIRS0450024DC14667827000W03

Article no.: 101351

Gross height [mm]	27.0
Gross width [mm]	330.0
Gross length [mm]	330.0
State of origin	AT

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article	Article no.
Wall profile AIR SIDE	**170886**
Mounting clip AIR SIDE	**170888**
Endcap set AIR SIDE	**170890**
Safety clip AIR SIDE	**170917**
Safety clip AIR MULTI	**170918**

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com

© BILTON International GmbH, Gewerbepark Harham 2, 5760 Saalfelden, Austria // Phone: +43 6582 71164 // Mail: office@biltongroup.com // www.biltongroup.com