


BILTON AIR TOP 850 2019

BLAIRT0850024DC14667830000W03

Article no.: 101375

BILTON

FOCUSED
ON
LINEAR
LIGHT




Lamp voltage



Luminous flux per meter



Max. length



Colour rendering index CRI

TENDER TEXT

BILTONAIR TOP 850 LED strip 24VDC 14,6W/m IP67 CRI>80 3000K WHITE 3m LED module BILTON AIR TOP 850 2019 Article 101375 Linear LED light strip on a flexible circuit board. Installation using appropriate mounting accessories in conjunction with Plug-&-Play connection system. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 50000 h . The BILTON AIR TOP 850 2019 LED-strip has a luminous flux of 850 lm at 14.6 W, resulting in an efficiency of 58 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 3000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 3000 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IP67 Smallest possible bending radius 200 mm Dimension (L x W x H): 3010.0 mm x 13.2 mm x 12.0 mm

TOP-FEATURES

- //__ Homogeneously illuminated light line with no visible light points
- //__ IP67 protection in highly flexible silicone jacket
- //__ Unlimited freedom of design (flexibly deformable and separable)



BILTON AIR TOP 850 2019

BLAIRT0850024DC14667830000W03

Article no.: 101375

MECHANICAL DATA

Net width [mm]	13.2
Net height [mm]	12.0
Net length [mm]	3010.0
Degree of protection (IP)	IP67
Colour	White
Distance [mm]	7.14
Distance relating to	LED to LED
Length of particular segments [mm]	50.0

ELECTRICAL DATA

Overall efficiency [lm/W]	58
Lamp power per meter [W]	14.6
Lamp voltage [V]	24
Input voltage range [V]	23 - 25
Voltage type	DC
Protection class	None

LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	850
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>80
Colour temperature [K]	3000

CONNECTION

Number of poles	2
Conductor cross section [mm²]	0.50
Max. length [mm]	3000.0

TEMPERATURE TECHNICAL DATA

Rated life time L80/B10 at 25 °C [h]	50000
Ambient temperature during operating [°C]	- 20 ... + 45
Ambient/storage temperature [°C]	- 20 ... + 50

PACKAGING INFORMATION

EAN	4250716933369
Article no.	101375
Customs tariff number	94054039
Length [mm]	3010.0

BILTON AIR TOP 850 2019

BLAIRT0850024DC14667830000W03

Article no.: 101375

Gross height [mm]	27.0
Gross width [mm]	330.0
Gross length [mm]	330.0
State of origin	AT

* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

NECESSARY ACCESSORIES

Article	Article no.
Profile AIR TOP	170885
Alu profile AIR TOP	171031
Mounting clip AIR TOP	170887
Endcap set AIR TOP	170889
Safety clip AIR MULTI	170918
Safety clip AIR TOP	170919

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com