## BL RGBW 2700K



#### BLCOL0700024DC07920RGB827C05

Article no.: 171140





Degree of protection (IP) Luminous flux per meter





Max. length

#### **TENDER TEXT**

BL Color 700 LED strip 24VDC 7,9W/m IP20 RGB + CRI>80 2700K 5m LED module BL RGBW 2700K Article 171140 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 36000 h . The BL RGBW 2700K LED-strip has a luminous flux of 700 lm at 7.9 W, resulting in an efficiency of 89 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 5000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of RGB + 2700 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM5 (MacAdams). The light strip can be separated every 100.0 mm, resulting in a LED distance of 14.30 mm. Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 10.0 mm x 1.6 mm















# BL RGBW 2700K



#### BLCOL0700024DC07920RGB827C05

Article no.: 171140

### MECHANICAL DATA

Net width [mm]	10.0
Net height [mm]	1.6
Net length [mm]	1000.0
Degree of protection (IP)	IP20
Colour	White
Distance [mm]	14.30
Distance relating to	LED to LED
Length of particular segments [mm]	100.0

### **ELECTRICAL DATA**

Overall efficiency [lm/W]	89
Lamp power per meter [W]	7.9
Lamp voltage [V]	24
Voltage type	DC
Protection class	III

## LIGHT TECHNICAL DATA

20
DCM5
80
RGB + 2700

## CONNECTION

Number of poles	5
Conductor cross section [mm²]	0.50
Max. length [mm]	5000.0

## TEMPERATURE TECHNICAL DATA

Rated life time L70/B50 at 25 °C [h]	36000
Ambient temperature during operating [°C]	- 20 + 45
Ambient/storage temperature [°C]	0 + 60

## PACKAGING INFORMATION

EAN	4250716940930
Article no.	171140
Customs tariff number	94054239
Length [mm]	5000.0
State of origin	CN

## BL RGBW 2700K

#### BILTON FOCUSED ON LINEAR

#### BLCOL0700024DC07920RGB827C05

Article no.: 171140

\* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of -/+ 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com