



3,5 - 24
V

Input voltage range

3150 MHz

Control signal

TENDER TEXT

BL LMS RGBW Controller 24VDC remote FUNK IP20 BILTON LEDON TechnologyRGBW Controller Article 171215 The controller RGBW Controller is operated with Radio frequency (RF) and is served with a Radio frequency (RF) . The controller and has an output voltage of 24 V .The power dissipation in stand-by is . Dimension (L x W x H): 175.0 mm x 45.0 mm x 27.0 mm

TOP-FEATURES

- //__ Remote radio control for switching, dimming and controlling BILTON LEDON Technology RGB and RGBW modules
- //__ Remote control incl. receiver (control)

Radio
frequency
(RF)

RGBW Controller

BLLMSRGBW024DC00FUNK00120
Article no.: 171215

MECHANICAL DATA

Colour	White
Material	Plastic

ELECTRICAL DATA

Control signal	Radio frequency (RF)
Input voltage range [V]	3,5 - 7
Voltage type	DC
Number of channels	4

TEMPERATURE TECHNICAL DATA

Ambient temperature during operating [°C]	- 30 ... + 50
---	---------------

PACKAGING INFORMATION

EAN	4250716942071
Article no.	171215
Customs tariff number	85437090
State of origin	CN

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com