


# BLONE 900 >90

BLO190900024DC088X6927000W05

Article no.: 101489

**BILTON**


FOCUSED  
ON  
LINEAR  
LIGHT



Lamp voltage



Luminous flux per meter



Max. length



Colour rendering index CRI

## TENDER TEXT

BL ONE 900 LED strip 24VDC 8,8W/m IPX6 CRI>90 2700K WHITE 5m LED module BLONE 900 >90 Article 101489 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LEDON Technology LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLONE 900 >90 LED-strip has a luminous flux of 820 lm at 8.8 W, resulting in an efficiency of 93 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 10500.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 120°. All this with a colour rendering index of >90 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 7.14 mm. Degree of protection IPX6 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.5 mm

## TOP-FEATURES

- //\_\_ Best light quality for shop lighting with CRI >90
- //\_\_ Improvement of homogeneity by 20 additional LEDs per meter
- //\_\_ Wide choice of light colors and lumen packages
- //\_\_ With a maximum module length of up to 10500.0 mm long, linear lighting lines can be implemented
- //\_\_ UL certification available



# BLONE 900 >90

BLO190900024DC088X6927000W05

Article no.: 101489

**BILTON**  
FOCUSED  
ON  
LINEAR  
LIGHT

## MECHANICAL DATA

|                                    |            |
|------------------------------------|------------|
| Net width [mm]                     | 8.0        |
| Net height [mm]                    | 1.5        |
| Net length [mm]                    | 5000.0     |
| Degree of protection (IP)          | IPX6       |
| Colour                             | White      |
| Net weight [g]                     | 50.4       |
| Distance [mm]                      | 7.14       |
| Distance relating to               | LED to LED |
| Length of particular segments [mm] | 50.0       |

## ELECTRICAL DATA

|                           |         |
|---------------------------|---------|
| Overall efficiency [lm/W] | 93      |
| Lamp power per meter [W]  | 8.8     |
| Lamp voltage [V]          | 24      |
| Input voltage range [V]   | 23 - 25 |
| Voltage type              | DC      |
| Protection class          | III     |

## LIGHT TECHNICAL DATA

|   |       |
|---|-------|
| Luminous flux per meter [lm]                                | 820   |
| Beam angle [°]  | 120   |
| Colour consistency (McAdam ellipse)                         | SDCM3 |
| Colour rendering index CRI                                  | >90   |
| Colour temperature [K]                                      | 2700  |
| Energy efficiency class provided exchangeable built-in lamp | F     |

## CONNECTION

|  |         |
|--|---------|
| Number of poles                            | 2       |
| Conductor cross section [mm <sup>2</sup> ] | 0.50    |
| Max. length [mm]                           | 10500.0 |

## TEMPERATURE TECHNICAL DATA

|   |               |
|---|---------------|
| Rated life time L80/B10 at 25 °C [h]      | 60000         |
| Ambient temperature during operating [°C] | - 20 ... + 45 |
| Ambient/storage temperature [°C]          | - 5 ... + 55  |
| Operation temperature at Tc [°C]          | - 5 ... + 60  |

## PACKAGING INFORMATION

|     |               |
|-----|---------------|
| EAN | 4250716934694 |
|-----|---------------|

# BLONE 900 >90

**BILTON**FOCUSED  
ON  
LINEAR  
LIGHT**BLO190900024DC088X6927000W05**

Article no.: 101489

|                       |          |
|-----------------------|----------|
| Article no.           | 101489   |
| Customs tariff number | 94054099 |
| Length [mm]           | 5000.0   |
| Gross weight [g]      | 179.2    |
| Gross height [mm]     | 18.0     |
| Gross width [mm]      | 200.0    |
| Gross length [mm]     | 200.0    |
| State of origin       | AT       |

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.biltongroup.com](http://www.biltongroup.com)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.biltongroup.com](http://www.biltongroup.com)