

BLONE 1300 >80

BLONE1300024DC112X6827000W20

Article no.: 100271





24 V	1300 lm	7500.0 mm	>80
Lamp voltage	Luminous flux per meter	Max. length	Colour rendering index CRI

TENDER TEXT

BILTONONE 1300 LED strip 24V DC 11,2W/m IPX6 CRI>80 2700K WHITE 20m LED module BLONE 1300 >80 Article 100271 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape. Dimmable using BILTON LED dimmer. Suitable for ambient temperatures from -20 ... +45 °C at a service life of 60000 h . The BLONE 1300 >80 LED-strip has a luminous flux of 1300 lm at 11.2 W, resulting in an efficiency of 116 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 7500.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 2700 K and a beam angle of 120°. All this with a colour rendering index of >80 and a Binning selection based on SDCM3 (MacAdams). The light strip can be separated every 50.0 mm, resulting in a LED distance of 8.30 mm. Degree of protection IPX6 Dimension (L x W x H): 20000.0 mm x 8.0 mm x 1.5 mm

TOP-FEATURES

//__ Wide range of applications for linear lighting in white

//__ Highly flexible LED light strip for general lighting tasks

//__ With a maximummodule length of up to 7500.0 mm long, linear lighting lines can be implemented

24 V | >80 | IPX6 | 2700 K | RoHS COMPLIANT 2002/95/EC | CE

Version: 20240328 // Errors and printing errors are reserved.
© BILTON International GmbH, Gewerbepark Harham 2, 5760 Saalfelden, Austria // Phone: +43 6582 71164 // Mail: office@biltongroup.com // www.biltongroup.com

BLONE 1300 >80

BLONE1300024DC112X6827000W20
Article no.: 100271

MECHANICAL DATA

Net width [mm]	8.0
Net height [mm]	1.5
Net length [mm]	20000.0
Degree of protection (IP)	IPX6
Colour	White
Net weight [g]	204.8
Distance [mm]	8.30
Length of particular segments [mm]	50.0

ELECTRICAL DATA

Overall efficiency [lm/W]	116
Lamp power per meter [W]	11.2
Lamp voltage [V]	24
Imput voltage range [V]	23 - 25
Voltage type	DC
Protection class	None

LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	1300
Beam angle [°]	120
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	>80
Colour temperature [K]	2700
Energy efficiency class provided exchangeable built-in lamp	A +

CONNECTION

Number of poles	2
Conductor cross section [mm²]	0.50
Max. length [mm]	7500.0

TEMPERATURE TECHNICAL DATA

Rated life time L80/B10 at 25 °C [h]	60000
Ambient temperature during operating [°C]	- 20 ... + 45
Ambient/storage temperature [°C]	- 5 ... + 55
Operation temperature at Tc [°C]	- 5 ... + 60

PACKAGING INFORMATION

Article no.	100271
Customs tariff number	94054099

© BILTON International GmbH, Gewerbepark Harham 2, 5760 Saalfelden, Austria // Phone: +43 6582 71164 // Mail: office@biltongroup.com // www.biltongroup.com

BLONE 1300 >80

BLONE1300024DC112X6827000W20

Article no.: 100271

Length [mm]	20000.0
Gross weight [g]	328.6
Gross height [mm]	18.0
Gross width [mm]	200.0
Gross length [mm]	200.0
State of origin	AT

* Specifications of the electrical and photometric parameters: All values are valid in the thermally steady state at 25 ° C ambient temperature under the standardized measuring environment of BILTON. Nominal lumen values differ for different light colors, these values can be found in the respective data sheets. All values can have tolerances of +/- 15 %.

NECESSARY ACCESSORIES

Article	Article no.
Feeder 2-pole 500mm	**170152**
Feeder 2-pole 2000mm	**170153**

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.biltongroup.com

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.biltongroup.com

© BILTON International GmbH, Gewerbepark Harham 2, 5760 Saalfelden, Austria // Phone: +43 6582 71164 // Mail: office@biltongroup.com // www.biltongroup.com