


# BL COR Pure COB

**BILTON**FOCUSED  
ON  
LINEAR  
LIGHT**BL COR PURE COB LED strip 980lm/m 24VDC 10W/m IP20 940 5m**

Article no.: 171846



Beam angle



Degree of protection (IP)



Length of particular segments




Colour

## TENDER TEXT

LED strip light LED type: COB 980 lm/m 24VDC 10W/m 98lm/W IP20 CRI>90 4000K; one-sided connection cable 50 cm, WHITE Colors and BLT label 5 meters LED module BL COR Pure COB Article 171846 Linear LED light strip on a flexible circuit board. Installation using self-adhesive heat-conducting adhesive tape with COB (chip-on-board) coating.. Suitable for ambient temperatures from -25 ... +40 °C at a service life of . The BL COR Pure COB LED-strip has a luminous flux of 980 lm at 10.0 W, resulting in an efficiency of 98 lm/W. At a nominal voltage of 24 V DC on the connection, a maximum module length of 5000.0 mm can be achieved. In terms of lighting, the module has a colour temperature of 4000 K and a beam angle of 142°. All this with a colour rendering index of >90 and a Binning selection based on (MacAdams). The light strip can be separated every 29.4 mm, resulting in a LED distance of . Degree of protection IP20 Dimension (L x W x H): 5000.0 mm x 8.0 mm x 1.6 mm

## TOP-FEATURES

- //\_ Dot-free Yellow LED light line with large beam angle 142°
- //\_ Color rendering >90
- //\_ Easy installation



# BL COR Pure COB

**BL COR PURE COB LED strip 980lm/m 24VDC 10W/m IP20 940 5m**

Article no.: 171846

## MECHANICAL DATA

Net width [mm]	8.0
Net height [mm]	1.6
Net length [mm]	5000.0
Degree of protection (IP)	IP20
Colour	Yellow
Net weight [g]	120
Length of particular segments [mm]	29.4

## ELECTRICAL DATA

Overall efficiency [lm/W]	98
Lamp power per meter [W]	10.0
Lamp voltage [V]	24
Voltage type	DC
Protection class	III

## LIGHT TECHNICAL DATA

Luminous flux per meter [lm]	980
Beam angle [°]	142
Colour rendering index CRI	>90
Colour temperature [K]	4000

## CONNECTION

Number of poles	2
Max. length [mm]	5000.0

## TEMPERATURE TECHNICAL DATA

Ambient temperature during operating [°C]	- 25 ... + 40
---	---------------

## PACKAGING INFORMATION

EAN	4250716948653
Article no.	171846
Customs tariff number	9405423990
Length [mm]	5000.0
State of origin	CN

\* Information about the electrical and lighting technology measurements: Performance data measured after 1 min. at 25 °C ambient temperature and a light colour of 4,000 K (or RGB). These values can have a tolerance value of +/- 15%. Module length at 24 V input voltage at the module and luminous flux drop 10% over the specified length.

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be

# BL COR Pure COB

**BILTON**

FOCUSED  
ON  
LINEAR  
LIGHT

**BL COR PURE COB LED strip 980lm/m 24VDC 10W/m IP20 940 5m**

Article no.: 171846

found at: [www.biltongroup.com](http://www.biltongroup.com)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.biltongroup.com](http://www.biltongroup.com)